

Technical Data Sheet

2026-01-09 (date of download)
2025-11-20 (last modified date)

NO ACIDIC FOODS


Product group: READY2COOK®
Name: 670ml Alu coated container - bulk transpac
Item number: 0066912000



Technical material:



Application:



Rim style:



Product specifications

Technical name	RECT.670ML.LACQ.BULK
Material category	ALUMINIUM
Shape	RECTANGULAR
Product category	TRAY
Compartment	1-COMPARTMENT
Application	Freezer, Microwave, Oven
Height	50 mm
Top out length	171 mm
Top out width	122 mm
Top in length	153 mm
Top in width	104 mm
Base length	140 mm
Base width	91 mm
Weight/1 pc.	13.28 g (+/-10%)
Weight/1000 pcs.	13.30 kg
Total volume	670 ml
Temperature	
Minimum inner temperature	-40 °C
Maximum inner temperature	200 °C
Minimum outer temperature	-40 °C
Maximum outer temperature	200 °C

Material & product features

Material	ALU COATED
Foil description	LACQUER
Inside lacquer/Outside lacquer	Yes/Yes
Lacquer type	In Polyester (BPA NIA) Out lacq. (BPA NIA)
Barrier/laminat	No/No
Color (in/out)	COLORLESS/COLORLESS
Tray features	N/A
Rim style	Heat seal curl
Closing options	Sealing film, Skin pack
Situation	Ready-to-heat, Ready-to-cook
Suitable for food contact	Yes
Sustainability details	
Designed to be recycled	Yes
Mono-material	Yes
Biodegradable	No
Biobased	No
Sourced from ASI	
Suitable for repeated use	No
Total recycled content	36% avg

Packaging

Packaging method	Bulk Transpac
Bag	
Quantity/Bag	168 pcs (+/- 2%)
EAN bag code	N/A
Carton	
Quantity/carton	16800 pcs (+/- 2%)
Carton volume	1.1810 m ³
Carton length	120 cm
Carton width	80 cm
Carton height	123 cm
Net weight/carton	223.0290 kg
Gross weight/carton	255.1290 kg
EAN carton code	5701022220371
Pallet	
Quantity/pallet	16800 pcs (+/- 2%)
Cartons/pallet	1 crt
Cartons/layer	1
Layers/pallet	1
Pallet height	123 cm
Net weight/pallet	255.1 kg
EAN pallet code	N/A

Technical Data Sheet

2026-01-09 (date of download)
2025-11-20 (last modified date)

NO ACIDIC FOODS

Product group: READY2COOK®
Name: 670ml Alu coated container - bulk transpac
Item number 0066912000



Material

- The aluminium foil contains a food approved lubricate, the amount is depending on the shape and complexity of the container.
- Be aware that containers with outside and/or inside lacquer can have limitations on the specified temperature. Lacquer is specified to app. 200°C, but time, food and other conditions may affect heat resistance, therefore it must be tested at the customer. For more information on specific food stuffs, see relevant DOC.

Application

- Aluminium containers are safe to use in microwave ovens constructed after 1983 following the instructions that can be found at: www.alufoil.org/about-alufoil/reference-library/aluminium-foil-and-microwave-ovens.html
- When used in any form of heating device (e.g., microwave oven, conventional oven, grill, etc.), the end-user must always refer to and follow the instructions provided by the heating device manufacturer. Plus Pack accepts no responsibility for misuse or deviation from such guidance.
- This container can be used in combination with a sealing film and/or skin pack film for product presentation and extended shelflife. To make sure the application is within the expectations, always make sure to do a thorough test.

Recycled content

- The recycled content in % is the secondary production aluminium part. This is a calculated average based on raw material supplier data for the last 2 calendar years. It can be subject to changes based on changes from our supplier.
- Be aware that the post-industrial-waste & post-consumer-waste is calculated according to third party information.

Packaging

- The number of packagings may vary, but the number is equalized by the total order.

Disposal

- The product and the packaging are made of a valuable material. Please recycle where possible and follow the local waste handling guidelines.